

MATERIAL SAFETY DATA SHEET

Anchor Seal, Inc.

POLYURETHANE

PREPOLYMER

Section 1. Chemical Product and Company Identification	
Product name/ U1580D (Part A) Trade Name POLYURETHANE PREPOLYMER	<i>IN CASE OF EMERGENCY:</i> INFOTRAC: 1-800-535-5053
Manufacturer ANCHOR-SEAL, Inc 54 Great Republic Drive Gloucester, MA 01930	INFORMATION: 1-800-669-5217
Date of Preparation: 11/20/12	Replaces: 8/30/10
Preparers Name Peter E. Spinney	

Section 2. Composition, Information on Ingredients			
<i>Component Information</i>		<i>Exposure Limits</i>	
<i>Chemical Name:</i>	<i>CAS#</i>	<i>TLV (ppm) ACGIH</i>	<i>OSHA PEL, TWA</i>
Modified MDI Pre-polymer	Trade Secret		

TLV™-Threshold Limit Value exposure (8 hour, time weighted average unless otherwise noted) established by the American Conference of Governmental Industrial Hygienists. PEL - OSHA Permissible Exposure Limit. N/E indicates that no exposure limit has been established.

Section 3. Hazards Identification				
WARNING! This product contains isocyanates, which readily react with body moisture causing eye and skin irritation. May cause allergic respiratory reaction. May cause skin sensitization and dermatitis. Avoid inhaling fumes.				
Potential Health Effects		Primary Routes of Exposure:		
X Skin contact	X Skin Absorption	X Eye Contact	X Inhalation	Ingestion
Routes of Exposure	Symptoms			
Inhalation	Inhalation of vapors can cause burning sensation in the respiratory tract with running nose, sore throat, coughing chest discomfort and reduced lung function.			
Skin	Can cause skin irritation such as blistering, swelling, redness and rashes.			
Eyes	Exposure to vapors and mist can cause irritation, pain, conjunctivitis and corneal edema.			
Ingestion	Harmful if swallowed. Can cause abdominal pain, nausea, vomiting and diarrhea.			
Chronic	Prolonged contact with skin can result in respiratory sensitization. Repeated inhalation exposure may cause lung damage and asthma.			
Carcinogenicity	OSHA: Not Regulated	NTP: Not Listed	IARC: Not Listed	

Section 4. First Aid Measures	
Eyes	Immediately wash the eyes with large amounts of water for at least 15 minutes, occasionally lifting the lower and upper lids. Get medical attention immediately.
Skin	Immediately wash the contaminated skin with soap and water. If this chemical penetrates the clothing, immediately remove the clothing, wash the skin with soap and water, and get medical attention.
Inhalation	Immediately move the exposed person to fresh air. If breathing is difficult, properly trained personnel may administer oxygen. Get medical if symptoms persist.
Ingestion	If large quantities have been swallowed, DO NOT INDUCE VOMITING. If victim is conscious and alert, give 2 - 4 cups of lukewarm water. Get medical attention.

MATERIAL SAFETY DATA SHEET

Anchor Seal, Inc.
PREPOLYMER

POLYURETHANE

Section 5. Fire Fighting Measures	
Extinguishing Media: X Water X Carbon Dioxide X Dry Chemical X Foam Alcohol Foam	
Flash Point	>200°F SETA Flash LEL: N/D UEL: N/D
Flammability Classification OSHA/NFPA	Class III B Liquid
Extinguishing Media	Carbon dioxide, dry chemical, foam.
Unusual Fire and Explosions Hazards	Isolate fire area and deny unnecessary entry. Fire fighters should wear positive-pressure self-contained breathing apparatus (SCBA) and protective clothing. Cool closed containers with WATER SPRAY to avoid explosion. Heat from fire can generate vapor and decomposition products that may cause a health hazard.

Section 7. Handling & Storage
Store material in a clean, cool, ventilated area away from all sources of ignition. Clean up spills at once. Keep container tightly closed when not in use. This product reacts readily with moisture generating heat and gas. Avoid mixing with water. Always wear protective equipment. Wash hands and other exposed areas thoroughly after handling. Provide appropriate ventilation/respiratory protection against nuisance dust during sanding/grinding of cured product.

Section 6. Accidental Release Measures
ISOLATE AREA OF THE SPILL! Eliminate all ignition sources. Soak up small spills with inert solids such as vermiculite or other absorbent materials. Shovel into suitable disposal container. Persons not wearing protective equipment should be excluded from the area of spill until cleanup has been completed.

Section 8. Exposure Controls/Personal Exposure	
Eye Protection	Avoid splashing. Wear chemical-resistant safety goggles or face shield. Contact lenses must not be worn.
Skin Protection	Chemical resistant synthetic rubber (neoprene, nitrile) gloves and other protective clothing are recommended to prevent repeated or prolonged skin contact.
Respiratory Protection	If personal exposure cannot be controlled below applicable limits by area ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in section 2.
Ventilation	General area ventilation is acceptable if the exposure is maintained below applicable exposure limits. (See Section 2) Local exhaust is recommended for confined areas. See 29 CFR 1910.146
Other Precautions	Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Section 9. Physical and Chemical Properties			
Percent Volatile Content by Volume (PBV) or Weight (PBW)	N/D	Specific Gravity (gm/cc)	1.14-1.21
VOC Content	N/D	Weight per Gallon	>9 lbs.
Boiling Point	>200°C	Evaporation Rate	N/D
Vapor Pressure (mm Hg)	0.000004 mmHg	Solubility in Water	Immiscible

MATERIAL SAFETY DATA SHEET

Anchor Seal, Inc.

POLYURETHANE

PREPOLYMER

Vapor Density (Air=1)	8.5	Appearance and Odor	Clear liquid, musty odor
-----------------------	-----	---------------------	--------------------------

Section 10. Stability and Reactivity

Stability	Stable
Conditions to Avoid	Protect from heat, sparks, flame and possible sources of ignition.
Incompatibility	Avoid contact with strong acids, bases, alcohol and copper alloys.
Hazardous Decomposition Products	Fumes produced when heated to decomposition may contain Carbon dioxide, carbon monoxide, aldehydes and other hazardous gases.
Hazardous Polymerization	Mixing large quantities of prepolymer and polyol will generate significant heat. Uncontrolled cure conditions may char and decompose the resultant polymer generating unidentified toxic fumes and vapors.

Section 11. Toxicological Information Acute Toxicity (see Section 3. for Exposure Symptoms)

Chemical Identity	ORAL LD 50	DERMAL LD 50	Inhalation LC 50
4,4'-Diphenylmethane-Diisocyanate	>5000 mg/kg (Rat)	>5000 mg/kg (Rabbit)	490 mg/m ³ 4 hours (Rat)

Section 12. Ecological Information

Material has not been tested for potential adverse effects to the environment.

Section 13 Disposal Considerations

RCRA: This product, if disposed as shipped, is not considered a hazardous waste as specified in 40 CFR 261. Dispose of in accordance with all applicable federal, state and local regulations.

Section 14 Transportation Information

This product, if offered for shipment, is regulated by USDOT 49 CFR Parts 171 - 180: Regulation of Hazardous Materials Transportation in Commerce.

Shipping Information	Liquid Plastic N.O.S.
Classification	Not Regulated in quantities less than 5000 lbs.
Identification	N/A
Packing Group	N/A
Label	N/A

Section 15. Regulatory Information

Regulations Governing Product:

Inventory Status: United States (TSCA) - All ingredients are on the inventory or exempt from listing.

SARA TITLE III

EPCRA 311/312 Tier II Chemical Inventory Reporting: Immediate (acute)

	Health	Flammability	Chemical Reactivity
HMIS Rating	2*	1	1

MATERIAL SAFETY DATA SHEET

Anchor Seal, Inc.

POLYURETHANE

PREPOLYMER

<i>Regulations Governing Ingredients</i>		<i>* Chronic Health Hazard</i>		
<i>Chemical Name:</i> <i>Modified MDI</i>	<i>CAS #/ Category#</i> <i>Trade Secret</i>	<i>CERCLA RQ</i>	<i>EPCRA 313 RQ</i>	<i>EPCRA 302 RQ EHS</i>

Section 16 Other Information

REFERENCES

CRC Press: Handbook of Chemical and Physical Constants by David R. Lide
Merck & Company: The Merck Index
Dictionary of Toxicology by Robert Lewis
J.J. Keller & Associates: Chemical Ratings Guide HMIS III
US Department of Transportation, Research and Special Programs Administration: Hazardous Materials Table

The information contained herein is given in good faith but no guarantee or warranty of any kind, expressed or implied, is made with respect to the information above. Anchor Seal, Inc. expressly disclaims any liability which may be incurred in using the information contained herein.