

# MATERIAL SAFETY DATA SHEET

**Anchor Seal, Inc.**

**MERCAPTAN CURING**

**AGENT**

<b>Section 1. Chemical Product and Company Identification</b>	
<b>Product name/ SY5822D (Part B)</b> <b>Trade Name Mercaptan Curing Agent</b> <b>Manufacturer</b> ANCHOR SEAL, Inc 54 Great Republic Drive Gloucester, MA 01930	<b>IN CASE OF EMERGENCY:</b> INFOTRAC: 1-800-535-5053 INFORMATION: 1 800-669-5217
<b>Date of Preparation:</b> 10/3/10	<b>Replaces:</b>
<b>Prepared By:</b> Peter E. Spinney	

<b>Section 2. Composition, Information on Ingredients</b>			
<i>Component Information</i>		<i>Exposure Limits</i>	
<i>Chemical Name</i>	<i>CAS#</i>	<i>TLV(ppm)ACGIH</i>	<i>OSHA PEL, TWA</i>
Mercaptan Mixture	Trade Secret	N/E	N/E

<b>Section 3. Hazards Identification</b>				
CAUTION! May cause eye irritation. May cause skin irritation with prolonged contact. Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Do not take internally.				
<b>Potential Health Effects</b>		Primary Routes of Exposure:		
X Skin contact	X Skin Absorption	X Eye Contact	X Inhalation	Ingestion
Routes of Exposure	Symptoms			
<b>Eyes</b>	Contact with product may cause irritation, pain and transient edema.			
<b>Skin</b>	Contact with product may cause irritation, itching and discomfort.			
<b>Inhalation</b>	Inhalation of vapor may cause irritation to the respiratory tract with coughing and chest pain.			
<b>Ingestion</b>	Swallowing this material can cause gastrointestinal irritation, nausea and vomiting.			
<b>Effects of Chronic Overexposure</b>	Prolonged or repeated exposure can cause sensitization resulting in itching, swelling or rashes on subsequent exposures.			
<b>Carcinogenicity</b>	OSHA: N/L	IARC: N/L	NTP: N/L	

<b>Section 4. First Aid Measures</b>	
<b>Eyes</b>	Immediately wash the eyes with large amounts of water for at least 15 minutes, occasionally lifting the lower and upper lids. Get medical attention immediately.
<b>Skin</b>	Immediately wash the contaminated skin with soap and water. If this chemical penetrates the clothing, immediately remove the clothing, wash the skin with soap and water, and get medical attention.
<b>Inhalation</b>	Immediately move the exposed person to fresh air. If breathing is difficult, properly trained personnel may administer oxygen. Get medical if symptoms persist.
<b>Ingestion</b>	If large quantities have been swallowed, DO NOT INDUCE VOMITING. If victim is conscious and alert, give 2 - 4 cups of lukewarm water. Get medical attention.

<b>Section 5. Fire Fighting Measures</b>
--

# MATERIAL SAFETY DATA SHEET

Anchor Seal, Inc.

MERCAPTAN CURING

## AGENT

<b>Extinguishing Media:</b>			
Water	X Carbon Dioxide	X Dry Chemical	X Foam      Alcohol Foam
<b>Flash Point</b>	>200°F SETA Flash    LEL: N/D      UEL: N/D		
<b>Flammability Classification OSHA/NFPA</b>	Flash Pt. N/A	Class	Liquid
<b>Extinguishing Media</b>	Carbon dioxide, dry chemical, foam.		
<b>Unusual Fire and Explosions Hazards</b>	Isolate fire area and deny unnecessary entry. Fire fighters should wear positive-pressure self-contained breathing apparatus ( SCBA) and protective clothing. Cool closed containers with WATER SPRAY to avoid explosion. Heat from fire can generate vapor and decomposition products that may cause a health hazard.		

### **Section 7. Handling & Storage**

Store material in a clean, cool, ventilated area away from all sources of ignition. Clean up spills at once. Keep container tightly closed when not in use. Always wear protective equipment. Wash hands and other exposed areas thoroughly after handling. Handle mixed resin and hardener in accordance with the potential hazard of the curing agent used. Provide appropriate ventilation/respiratory protection against nuisance dust during sanding/grinding of cured product.

### **Section 6. Accidental Release Measures**

ISOLATE AREA OF THE SPILL! Eliminate all ignition sources. Soak up small spills with inert solids such as vermiculite or other absorbent materials. Shovel into suitable disposal container. Persons not wearing protective equipment should be excluded from the area of spill until cleanup has been completed.

### **Section 8. Exposure Controls/Personal Exposure**

<b>Eye Protection</b>	Avoid splashing. Wear chemical-resistant safety goggles or face shield. Contact lenses must not be worn.
<b>Skin Protection</b>	Chemical resistant synthetic rubber (neoprene, nitrile) gloves and other protective clothing is recommended to prevent repeated or prolonged skin contact.
<b>Respiratory Protection</b>	If personal exposure cannot be controlled below applicable limits by area ventilation, wear a properly fitted organic vapor/particulate respirator approved by NIOSH/MSHA for protection against materials in section 2.
<b>Ventilation</b>	General area ventilation is acceptable if the exposure is maintained below applicable exposure limits. ( See Section 2) Local exhaust is recommended for confined areas. See 29 CFR 1910.146
<b>Other Precautions</b>	Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

### **Section 9. Physical and Chemical Properties**

<b>Percent Volatile Content by Volume (PBV) or Weight (PBW)</b>	N/A	<b>Specific Gravity (gm/cc)</b>	1.15
<b>VOC Content ( less water) Note 1</b>	N/A	<b>Weight per Gallon</b>	9
<b>Boiling Point</b>	>200C	<b>Evaporation Rate</b>	N/A

# MATERIAL SAFETY DATA SHEET

Anchor Seal, Inc.

MERCAPTAN CURING

## AGENT

Vapor Pressure (mm Hg)	1 mbar at 10C (50F)	Solubility in Water	partially
Vapor Density (Air=1)	>1	Appearance and Odor	Viscous liquid, sulfur odor

### Section 10. Stability and Reactivity

Stability	Stable
Conditions to Avoid	Protect from heat, sparks, flame and possible sources of ignition.
Incompatibility	Avoid contact with strong acids and bases
Hazardous Decomposition Products	Fumes produced when heated to decomposition may contain Carbon dioxide, carbon monoxide, aldehydes and other hazardous gases.
Hazardous Polymerization	Mixing large quantities of resin and hardener will generate significant heat. Uncontrolled cure conditions may char and decompose the resin generating unidentified toxic fumes and vapors.

### Section 11. Toxicological Information Acute Toxicity (see Section 3. for Exposure Symptoms)

Chemical Identity	ORAL LD 50	DERMAL LD 50	Inhalation LC 50
Mercaptan / amine mixture	N/E	N/E	N/E

### Section 12. Ecological Information

Material has not been tested for potential adverse effects to the environment.

### Section 13 Disposal Considerations

RCRA: This product, if disposed as shipped, is not considered a hazardous waste as specified in 40 CFR 261. Dispose of in accordance with all applicable federal, state and local regulations.

### Section 14 Transportation Information

This product if offered for shipment is **not regulated** by US DOT 49 CFR Parts 171 - 180: Regulation of Hazardous Materials Transportation in Commerce.

Shipping Information	Liquid plastic N.O.S.
Classification	N/A
Identification	N/A
Packing Group	N/A
Label	None required

### Section 15. Regulatory Information

Regulations Governing Product:

Inventory Status: United States (TSCA) - All ingredients are on the inventory or exempt from listing.

SARA TITLE III

EPCRA 311/312 Tier II Chemical Inventory Reporting:	Immediate (acute)		
	Health	Flammability	Chemical Reactivity

# MATERIAL SAFETY DATA SHEET

Anchor Seal, Inc.

MERCAPTAN CURING

## AGENT

HMIS	2	1	0	
<i>Regulations Governing Ingredients</i>				
<i>Chemical Name</i>	<i>CAS #/ Category#</i>	<i>CERCLA RQ</i>	<i>EPCRA 313 RQ</i>	<i>EPCRA 302 RQ EHS</i>

### ***Section 16 Other Information***

#### REFERENCES

CRC Press: Handbook of Chemical and Physical Constants by David R. Lide  
Merck & Company: The Merck Index  
Sigma-Aldrich Company: Aldrich Handbook of Fine Chemicals  
Dictionary of Toxicology by Robert Lewis  
US Department of Transportation, Research and Special Programs Administration: Hazardous Materials Table

The information contained herein is given in good faith but no guarantee or warranty of any kind, expressed or implied is made with respect to the information above. Anchor-Seal, Inc. expressly disclaims any liability that may be incurred in using the information contained herein.